

CEILING LOUDSPEAKER

# Quam C5/BU/W/VC

C5/BU/W/VC consists of an 8" O.D., dual cone loudspeaker with a 5 oz. magnet and a 5W, 25/70V, multi-tap transformer. It includes a screwdriver or detachable knob (knob included) adjusted volume control and a round, screw-mount baffle with a white, powder coat finish.



<b>APPLICATION</b>	<b>Intended Use:</b> <b>Program Material:</b>	Indoor environment Signal tones, voice and music
<b>AUDIO PERFORMANCE</b>	<b>Average Sensitivity:</b> <b>Loudspeaker Power Rating:</b> <b>Maximum Power Rating:</b> <b>Calculated Output:</b> <b>Magnet Type &amp; Weight:</b> <b>Frequency Response:</b> <b>Nominal Coverage Angle:</b> <b>Audio Connection:</b>	92 dB SPL, 1W/1M 12W RMS, EIA 426A Standard 15W @ 8 Ohms 99dB SPL, 5W/1M BeFe Ceramic, 5 oz. Nominal 65Hz - 17kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads
<b>COMPONENT</b>	<b>Dimensions:</b> <b>Combined Weight:</b> <b>Loudspeaker Model:</b> <b>Loudspeaker Specs:</b> <b>Transformer:</b> <b>Baffle:</b> <b>Finish:</b> <b>Other:</b>	12 7/8" (Diameter) x 2 1/2" (D) 3.5 lbs. 8C5PAX 8" O.D. loudspeaker, 5 oz. magnet TBLU: 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5.0W) BR8W: round, steel, screw-mount White powder coat finish Volume control knob included
<b>RECOMMENDED QUAM COMPONENTS</b>	<b>Enclosures:</b> <b>Mounting Supports:</b>	ERD-8, ERD8U SSB-2, SSB-3, SSB-7

