

VANDAL RESISTANT LOUDSPEAKER

Quam H16/RVP

H16/RVP is a horn assembly with a double re-entrant, compression horn with a 16W, 25/70V integrated transformer, and a round, stud mount, vandal resistant, steel baffle. Mounting hardware is #8-32 'pin-in-torx.'



APPLICATION	Intended Use: Program Material: Installation:	Indoor environment Signal tones, voice and music Ceiling mount
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	96dB SPL, 1W/ 1M 16W RMS, EIA 426A Standard 108dB SPL, 16W/ 1M BeFe Ceramic, 10 oz. Nominal 350Hz - 10kHz, EIA 426A Standard 90° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads
COMPONENT	Dimensions: Weight: Loudspeaker Model: Loudspeaker Specs: Transformer: Baffle: Finish:	12 7/8" (Diameter) x 3 11/16" (H) 6 lbs. Integral to unit 8" O.D. loudspeaker, 10 oz. magnet 16W, 25/70V, with 5 taps (1W, 2W, 4W, 8W, 16W) BR8VP: round, steel, stud-mount White powder coat finish
RECOMMENDED QUAM COMPONENTS	Enclosures: Mounting Supports:	ERD-8, ERD8U SSB-2, SSB-3, SSB-7

