

Quam SYSTEM 14

SYSTEM 14 is a complete, shallow depth, lightweight, 1' x 2' ceiling tile replacement loudspeaker system consisting of an 8" O.D., foam edge, coaxial loudspeaker with a 10 oz. magnet and a 10W, 70V, low loss transformer. The molded fiber enclosure is 617 CID. The SYSTEM 14 has a powder coated steel baffle with standard perforation and four (4) seismic tie-off points. The cable clamp and one (1), 24", "T" rail are included. No assembly required.



APPLICATION	Intended Use:	Indoor environment
	Program Material:	Signal tones, voice, and music
	Installation:	Mounted parallel to floor plane in a 24" wide suspended ceiling tile grid
AUDIO PERFORMANCE	Average Sensitivity:	95dB SPL, 1W/1M
	Loudspeaker Power Rating:	20W RMS, EIA 426A Standard
	Maximum Power Rating:	15W @ 8 Ohms
	Calculated Output:	105dB SPL, 10W/1M
	Magnet Type & Weight:	BeFe Ceramic, 10 oz. Nominal
	Frequency Response:	40Hz - 20kHz, EIA 426A Standard
	Nominal Coverage Angle:	100° Included Angle, -6dB/2kHz, Half Space
	Audio Connection:	4", Color-coded, Pre-tinned Leads
COMPONENT	Dimension:	3 1/2" (H) x 23 13/16" (W) x 11 13/16" (D)
	Weight:	4.60 lbs.
	Loudspeaker Model:	8C10FECO
	Loudspeaker Specs:	8" O.D., loudspeaker, 10 oz. magnet
	Transformer:	TCH70; 10W, 70V, with 5 taps (0.63W, 1.25W, 2.5W, 5W, 10W)
	Integral Enclosure:	617 CID molded fiber
	Grille:	Standard perforated steel with four (4) seismic tie-off points
	Finish:	White powder coat finish

