

VANDAL RESISTANT LOUDSPEAKER

Quam SYSTEM 2VP

SYSTEM 2VP is a complete, vandal resistant loudspeaker system consisting of an 8" O.D., moisture resistant loudspeaker with a 10 oz. magnet and a 5W, 25/70V transformer mounted on a square, stud mount, vandal resistant, steel baffle with a slanted, steel, vandal resistant, surface mount enclosure with four (4) 8-32 threaded inserts, a single 1/2" conduit entrance, and two (2) Wiremold knockouts. Three (3) interwoven, steel security screens are mounted between the faceplate and loudspeaker. Tamper resistant, 8-32 x 1" 'pin-in-torx' hardware included. White powder coat finish.



APPLICATION	Intended Use: Program Material: Installation:	Indoor or protected outdoor environment Signal tones, voice, and music Vertical surface mount, downward firing
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	94dB SPL, 1W/1M 20W RMS, EIA 426A Standard 101dB SPL, 5W/1M BeFe Ceramic, 5 oz. Nominal 80Hz - 8kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads
COMPONENT	Dimensions: Weight: Loudspeaker Model: Loudspeaker Specs: Transformer: Baffle: Security: Enclosure: Finish: Other:	11 5/8" (H) x 11 5/8" (W) x 5 3/8" (D) 13 lbs. 8C10PAOT 8" O.D., moisture resistant loudspeaker TBLU; 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5W) BS8VP: square Three (3) interwoven, steel screens mounted between faceplate and loudspeaker SE2WVP White powder coat finish Tamper resistant, 8-32x1" 'pin-in-torx' hardware included

