

# Quam SYSTEM 5/25RSRJ

SYSTEM 5/25RSRJ is a complete, shallow depth, lightweight, 1' x 2' ceiling tile replacement loudspeaker system consisting of an 8" O.D., dual cone loudspeaker with a 5 oz. magnet, 4W, 25V rotary select transformer, and a dual RJ45 input connection jack. The molded fiber enclosure is 617 CID. The SYSTEM 5/25RSRJ has a powder coated steel baffle with standard perforation and four (4) seismic tie-off points. One (1), 24", "T" rail is included. No assembly required.



<b>APPLICATION</b>	<b>Intended Use:</b> <b>Program Material:</b> <b>Installation:</b>	Indoor environment Signal tones, voice, and music Mounted parallel to floor plane in a 24" wide suspended ceiling grid
<b>AUDIO PERFORMANCE</b>	<b>Average Sensitivity:</b> <b>Loudspeaker Power Rating:</b> <b>Maximum Power Rating:</b> <b>Calculated Output:</b> <b>Magnet Type &amp; Weight:</b> <b>Frequency Response:</b> <b>Nominal Coverage Angle:</b> <b>Audio Connection:</b>	92dB SPL, 1W/1M 12W RMS, EIA 426A Standard 15W @ 8 Ohms 98dB SPL, 4W/1M BeFe Ceramic, 5 oz. Nominal 65Hz - 17kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half Space Integrated dual RJ45 Sockets (audio input to pins 1 and 2)
<b>COMPONENT</b>	<b>Dimension:</b> <b>Weight:</b> <b>Loudspeaker Model:</b> <b>Loudspeaker Specs:</b> <b>Transformer:</b> <b>Integral Enclosure:</b> <b>Grille:</b> <b>Finish:</b>	3 1/2" (H) x 23 13/16" (W) x 11 13/16" (D) 3.95 lbs. 8C5PAX 8" O.D. loudspeaker, 5 oz. magnet 4W, 25V, rotary select with 5 taps (0.25W, 0.50W, 1W, 2W, 4W) 617 CID molded fiber Standard perforated steel with four (4) seismic tie-off points White powder coat finish

