

Quam CIS2/8

The CIS2/8 is a 3-gang, vandal resistant call-in station with integrated 8 Ohm speaker/microphone and a momentary contact (normally open), pushbutton callswitch. With a tamper resistant, heavy gauge, stainless steel faceplate and three (3) interwoven steel screens to protect the speaker, the CIS2/8 provides a very durable, high security call station for the most challenging applications. Tamper resistant, #6-32 x 1", 'pin-in-torx' screws are included.



APPLICATION	Intended Use: Program Material: Mounting:	Indoor environment Signal tones and voice 3-gang electrical box
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Maximum Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	87dB SPL, 1W/ 1M 4W RMS, EIA 426A Standard 5W @ 8 Ohms 93dB SPL, 5W/ 1M BeFe Ceramic, 2.35 oz. Nominal 300Hz - 10kHz, EIA 426A Standard 90° Included Angle, -6dB/2kHz, Half Space 0.205" Spade Lugs
COMPONENT	Dimension: Weight: Loudspeaker Model: Loudspeaker Specs: Finish: Material: Callswitch: Electrical Connection: Other:	5 1/2" (H) x 7 1/2" (W) x 1 15/16" (D) 3 lbs. 30C25Z8OT 3" O.D. loudspeaker Brushed 12 gauge, stainless steel faceplate Chrome plated button, momentary contact Screw-down, pinch Three (3) interwoven, steel screens mounted between faceplate and loudspeaker, four (4), tamper resistant, #6-32 x 1", 'pin-in-torx' screws included
RECOMMENDED QUAM COMPONENTS	Enclosures: Custom Engraving & Fill:	Surface Mount — SE3GVP, SE10GVP Contact the factory for details and lead times

