

Quam CIS4/45

The CIS4/45 is a 2-gang, vandal resistant call-in station with integrated speaker/microphone consisting of a 2.5" square frame loudspeaker with a 2.35 oz. ceramic magnet and a phenolic impregnated, moisture resistant cone. It is equipped with an 45 Ohm loudspeaker and a momentary contact (normally open), push-to-call, switch. Three (3) interwoven, steel security screens are mounted between the 12 gauge, brushed stainless steel faceplate and loudspeaker. Tamper resistant, #6-32 x 1", 'pin-in-torx' screws are included.



APPLICATION	Intended Use: Program Material: Mounting:	Indoor or protected outdoor environment Signal tones and voice 2-gang electrical box
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Maximum Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	87dB SPL, 1W/1M 4W RMS, EIA 426A Standard 5W @ 45 Ohms 93dB SPL, 5W/1M BeFe Ceramic, 2.35 oz. Nominal 200Hz - 8kHz, EIA 426A Standard 90° Included Angle, -6dB/2kHz, Half Space 0.205" Spade Terminals
COMPONENT	Dimension: Weight: Loudspeaker Model: Loudspeaker Specs: Finish: Material: Callswitch: Electrical Connection: Other:	4 1/2" (H) x 4 1/2" (W) x 1 3/4" (D) 3 lbs. 25C25Z450T 2.5" O.D., 45 Ohm loudspeaker Brushed 12 gauge, stainless steel faceplate Chrome plated button, momentary contact Screw-down, pinch Three (3) interwoven, steel screens mounted between faceplate and loudspeaker, four (4), tamper resistant, #6-32 x 1", 'pin-in-torx' screws included
RECOMMENDED QUAM COMPONENTS	Enclosures: Custom Engraving & Fill:	Surface Mount — SE7GVP, SE8GVP, SE9GVP Contact the factory for details and lead times

