

Quam CIS8/25

The CIS8/25 is a 2-gang, vandal resistant, hands free intercom station with a 2.5", square frame, 1W, 25V loudspeaker that has a 2.35 oz. ceramic magnet and a moisture resistant cone. With a tamper resistant, heavy gauge, stainless steel faceplate and three (3) interwoven steel screens to protect the speaker, the CIS8/25 provides a very durable, high security call station for the most challenging applications. Tamper resistant, #6-32 x 1", 'pin-in-torx' screws are included.



APPLICATION	Intended Use: Program Material: Mounting:	Indoor or protected outdoor environment Signal tones and voice 2-gang electrical box
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Maximum Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	87dB SPL, 1W/ 1M 4W RMS, EIA 426A Standard 5W @ 8 Ohms 93dB SPL, 5W/ 1M BeFe Ceramic, 2.35 oz. Nominal 200Hz - 6kHz, EIA 426A Standard 90° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads
COMPONENT	Dimension: Weight: Loudspeaker Model: Loudspeaker Specs: Transformer: Finish: Material: Other:	4 1/2" (H) x 4 1/2" (W) x 1 3/4" (D) 3 lbs. 25C25Z8OT 2.5" square frame, moisture resistant loudspeaker 1W, 25V with 3 taps (0.25W, 0.5W, 1W) Brushed 12 gauge, stainless steel faceplate Three (3) interwoven, steel screens mounted between faceplate and loudspeaker, four (4), tamper resistant, #6-32 x 1", 'pin-in-torx' screws are included
RECOMMENDED QUAM COMPONENTS	Enclosures: Custom Engraving & Fill:	Surface Mount — SE6GVP, SE7GVP Contact the factory for details and lead times

